

Self Adhesive Sheets Technical Data Sheet



FEATURES

Navitek Self Adhesive Sheets, designed specially to protect and cover surfaces, constructed with a non toxic acrylic water-based adhesive cover a PVC film with a back of silicone paper, this PVC cover is rigid and strong giving to the protection film a great mechanic resistance.

The film help to protect strongly for a longtime over many surfaces. Very resistant to folding and to the yellowing with the pass of time.



PRODUCT APPLICATION

Highly recommended for school and office duties. To protect and cover a broad range of surfaces as credentials, important documentation, plain surfaces and more.



COLORS

Natural ●



SUGGESTION

Is essential that the surface on which the product is applied is clean, dry and free of grease, oil and other contaminants.



LIFETIME AND STORAGE

The lifetime of this product is 1 year since fabrication, keeping it in its original boxes away from heat sources as: Direct sunlight or shelves next to exterior roofs.

The floor's cold and humidity could affect the product performance, the suitable conditions for storage are: 69,8 °F and 51% of relative humidity. We recommend rotating the stock in the practice of "first in, first out".

Composition		Specification	
Substrate		Rigid PVC	
Backing		Siliconized Paper	
Adhesive		Water-Based	
Adhesive Activation		Pressure Sensitive	
Composition	Metric Unit	Standard Unit	Test Method
Substrate Thickness + Dry Adhesive	145 microns	5.7 mils / 5 points	PSTC-133
Release Liner Thickness	125 microns	4.9 mils / 4.9 points	PSTC-133
Total Thickness	270 microns	10.6 ± 0.078 mils / 10.6 points	PSTC-133
Organic Solvent's Composition	265%	0%	N/A
Adhesive Properties	Metric Unit (Minimum Value)	Standard Unit (Minimum Value)	Test Method
Adhesion to Steel 180° (Peel)	400 g/inches	14 oz/inches	PSTC-101
Loop Tack (Stickness)	600g/inches	21 oz/inches	PSTC-16
Shear 1"x1"x1kg (Holding Power)	5 hours	5 hours	PSTC-107
Thermic / Electric Properties	Metric Unit	Standard Unit	Test Method
Minimum Temperature of Application	0°C	32° F	NTK
Maximum Temperature of Application	35 °C	95 °F	NTK
Label Measurements	Metric Unit Specification	Standard Unit Specification	
Width	25 cm	10 inches	
Height	33 cm	13 inches	

Note: For special colors and measures, please contact our sales agent.



IMPORTANT NOTICE: The technical properties outlined are typical values and are not considered as specifications. Our terms and conditions of sale apply exclusively to orders and are excluding any liability for damages and injury of any kind, including consequential damages exceeding the purchase price. These properties are based on tests or conventional standards, PSTC, ASTM, NOM, Navitek's Technologies. It's important that the purchaser make its own test to determine the suitability of the product is to be use, no one is authorized by us to make guarantees orally. We reserve the right to makechanges without notice or obligation in our products and publications.

Warranties and Limited Remedies:

Navilux, S.A. de C.V. warrants that each Navitek product meets the applicable Navitek specifications at the time Seller ships the product.

Individual products may have additional or different warranties, as stated on Navitek product packaging, package inserts, price pages or literature. Unless stated otherwise, if any product does not meet the applicable Navitek specification at the time of shipment, Navilux, S.A. de C.V.'s entire liability and purchaser's exclusive remedy will be replacement of Navitek product.

THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

Notice of defect must be received by Navilux, S.A. de C.V. within 90 days after the goods arrive at the designated place. Navilux, S.A. de C.V. has no obligations under this warranty with respect to products that have been modified through misuse, abuse, accident, neglect or mishandling by user or others.

Limitation of Liability:

Except where prohibited by law, Navilux, S.A. de C.V. will not be liable for any loss or damage arising from any Navitek product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. User is solely responsible for determining whether a Navitek product is fit for a particular purpose and suitable for user's method of application.