



FEATURES

The Navitek 14 Day Masking Tape is specially formulated and designed to withstand exposure to sunlight for 14 days with a clean and easy removal on a wide variety of surfaces. Adheres easily to surfaces and remains intact until the removal. Conformable, consistent and easy to unwind. It performs well in a wide variety of applications where a gentle removal is required. It is removed without breaking.



PRODUCT APPLICATION

Excellent for paint masking on multiple surfaces, including painting walls, woodwork, glass and metal. Designed for indoor and outdoor application.



COLOR

Blue



SUGGESTION

For its correct application it is essential that the surface on which the adhesive tape will be applied is clean, dry and free of grease, oil and other contaminants.



LIFETIME AND STORAGE

The lifetime of this product is 1 year since fabrication, keeping it in its original boxes away from heat sources as: Direct sunlight or shelves next to exterior roofs. The floor's cold and humidity could affect the product performance, the suitable conditions for storage are: 69,8 °F and 51% of relative humidity. We recommend rotating the stock in the practice of "first in, first out".

Composition		Specification	
Backing		Creped Paper	
Adhesive		Rubber - Resin	
Adhesive Activation		Pressure Sensitive	
Composition	Metric Unit	Standard Unit	Test Method
Total Weight	100 ± 10% g/m ²	62 ± 10% Lbs/ream	NTK
Total Thickness	125 ± 10% microns	4.9 ± 10% mils	PSTC-133
Organic Solvent's Composition	<1 %	<1 %	N/A
Adhesive Properties		Metric Unit (Minimum Value)	Standard Unit (Minimum Value)
Adhesion to Steel 180° (Peel)		600 g/inches	21.2 oz/inches
Loop Tack (Stickiness)		500 g/inches	17.6 oz/inches
Shear 1"x1"x1kg (Holding Power)		25 hours	25 hours
Primary Physical Properties		Metric Unit	Standard Unit
Tensile Strength		35 ± 20% N/cm	20 ± 20% lb/inches
Elongation		7% minimum	7% minimum
Standard Sizes	Metric Unit Specification	Standard Unit Specification	
Width	12, 18, 24, 36, 48 mm	1/2, 3/4, 1, 1 1/2, 2 inches	
Length	50, 55 m	55, 60 yards	

Note: For special colors and measures, please contact our sales agent.



Warranties and Limited Remedies:

Navilux, S.A. de C.V. warrants that each Navitek product meets the applicable Navitek specifications at the time Seller ships the product.

Individual products may have additional or different warranties, as stated on Navitek product packaging, package inserts, price pages or literature. Unless stated otherwise, if any product does not meet the applicable Navitek specification at the time of shipment, Navilux, S.A. de C.V.'s entire liability and purchaser's exclusive remedy will be replacement of Navitek product.

THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

Notice of defect must be received by Navilux, S.A. de C.V. within 90 days after the goods arrive at the designated place. Navilux, S.A. de C.V. has no obligations under this warranty with respect to products that have been modified through misuse, abuse, accident, neglect or mishandling by user or others.

Limitation of Liability:

Except where prohibited by law, Navilux, S.A. de C.V. will not be liable for any loss or damage arising from any Navitek product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. User is solely responsible for determining whether a Navitek product is fit for a particular purpose and suitable for user's method of application.