

581 / 582 / 583

Printed Tape 500: Hotmelt (1 to 3 inks)

Technical Data Sheet

FEATURES

Manufactured with bioriented polypropylene that give to the tape a great resistance to tension and breaking, with pressure sensitive acrylic water-based adhesive that offers high resistance and confiability. Customized printed with designs and logos in a broad range of colors. (Contact your local sales representative) Flexographic: Printed over the tape, reverse side of the adhesive with a maximum of 3 inks.

PRODUCT APPLICATION

To distinguish, advertise, differentiate products and packages with high quality printings. Can be printed with information as: Name and address of the company or branches, security text, customized information. Can help to distinguish warehouses, also is useful for publicity campaigns, promote products and more. Can be use in automatic or semi-automatic case sealers.

COLORS

Clear  Tan  White 

SUGGESTION


Is essential that the surface on which the tape is applied is clean dry and free of grease, oil and other contaminants.

LIFETIME AND STORAGE

The lifetime of this product is 3 months since fabrication, keeping it in its original boxes away from heat sources as: Direct sunlight or shelves next to exterior roofs.

The floor's cold and humidity could affect the product performance, the suitable conditions for storage are: 69, 8 °F and 51% of relative humidity.

We recommend rotating the stock in the practice of "First in, first out".

Composition		Specification	
Backing	BOPP (Bi Oriented Polypropylene)		
Adhesive	Hotmelt		
Adhesive Activation	Pressure Sensitive		
Composition	Metric Unit	Standard Unit	Test Method
Backing Thickness	25 microns	1.0 mils	PSTC-133
Dry Adhesive Thickness	13 microns	0.5 mils	PSTC-133
Total Thickness	38 ± 2 microns	1.5 ± 0.079 mils	PSTC-133
Organic Solvent's Composition	0 %	0 %	N/A
Adhesive Properties	Metric Unit (Minimum Value)	Standard Unit (Minimum Value)	Test Method
Adhesion to Steel 180° (Peel)	900 g/inches	32 oz/inches	PSTC-101
Loop Tack (Stickness)	1100 g/inches	39 oz/inches	PSTC-16
Shear 1"x1"x1kg (Holding Power)	50 hours	50 hours	PSTC-107
Primary Physical Properties	Metric Unit	Standard Unit	Test Method
Tensile Strength	35 ± 10% N/cm	20 ± 10% lb/inches	PSTC-131
Elongation	150 ± 20 %	150 ± 20 %	PSTC-131
Thermic / Electric Properties	Metric Unit	Standard Unit	Test Method
Minimum Temperature of Application	0 °C	32 °F	NTK
Maximum Temperature of Application	35 °C	95 °F	NTK
Measures 	Metric Unit	Standard Unit	
Width	12, 24, 36, 44, 48, 72 mm	0.47, 0.94, 1.41, 1.9, 2.83 inches	
Length	50, 100, 150, 910 m	55, 110, 166, 1000 yards	

Note: For special colors and measures, please contact our sales agent.



IMPORTANT NOTICE: The technical properties outlined are typical values and are not considered as specifications. Our terms and conditions of sale apply exclusively to orders and are excluding any liability for damages and injury of any kind, including consequential damages exceeding the purchase price. These properties are based on tests or conventional standards, PSTC, ASTM, NOM, Navitek's Technologies. It's important that the purchaser make its own test to determine the suitability of the product is to be use, no one is authorized by us to make guarantees orally. We reserve the right to makechanges without notice or obligation in our products and publications.

Warranties and Limited Remedies:

Navilux, S.A. de C.V. warrants that each Navitek product meets the applicable Navitek specifications at the time Seller ships the product.

Individual products may have additional or different warranties, as stated on Navitek product packaging, package inserts, price pages or literature. Unless stated otherwise, if any product does not meet the applicable Navitek specification at the time of shipment, Navilux, S.A. de C.V.'s entire liability and purchaser's exclusive remedy will be replacement of Navitek product.

THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

Notice of defect must be received by Navilux, S.A. de C.V. within 90 days after the goods arrive at the designated place. Navilux, S.A. de C.V. has no obligations under this warranty with respect to products that have been modified through misuse, abuse, accident, neglect or mishandling by user or others.

Limitation of Liability:

Except where prohibited by law, Navilux, S.A. de C.V. will not be liable for any loss or damage arising from any Navitek product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. User is solely responsible for determining whether a Navitek product is fit for a particular purpose and suitable for user's method of application.