



FEATURES

Anti Slip Tape designed with a rough aluminum oxide coating on a PVC base that prevents slips and falls. For use on multiple surfaces thanks to its high performance acrylic adhesive. Excellent durability both indoors and outdoors.



PRODUCT APPLICATION

Stairs, loading and unloading ramps, entrances, steps, ceramic and concrete floors, vehicles, skateboards, surfboards, bathrooms, etc.



COLORS

Black ● Black / Yellow ●



SUGGESTION

Is essential that the surface on which the tape is applied is clean, dry and free of grease, oil and other contaminants.



LIFETIME AND STORAGE

The lifetime of this product is 1 year since fabrication, keeping it in its original boxes away from heat sources as: Direct sunlight or shelves next to exterior roofs.

The floor's cold and humidity could affect the product performance, the suitable conditions for storage are: 69,8 °F and 51% of relative humidity. We recommend rotating the stock in the practice of "first in, first out".

Composition		Specification	
Substrate	PVC		
Liner	Siliconized Liner		
Adhesive	Acrylic		
Adhesive Activation	Pressure Sensitive		
Composition	Metric Unit	Standard Unit	Test Method
Liner Thickness	149 microns	5.87 mils	PSTC-133
Total Thickness	800 microns	31.5 mils	PSTC-133
Organic Solvent's Composition	0%	0%	PSTC-133
Adhesive Properties	Metric Unit (Minimum Value)	Standard Unit (Minimum Value)	Test Method
Adhesion to Steel 180° (Peel)	815 g/inches	28.7 oz/inches	PSTC-101
Loop Tack (Stickness)	1850 g/inches	65.2 oz/inches	PSTC-16
Shear 1"x1"x1kg (Holding Power)	18 hours	18 hours	PSTC-107
Primary Physical Properties	Metric Unit	Standard Unit	Test Method
Tensile Strength	20 N/cm	11.4 lb/inches	PSTC-131
Elongation	3%	3%	PSTC-131
Standard Sizes	Metric Unit	Standard Unit	
Width	25mm / 50 mm	1 inch / 2 inches	
Length	9m / 18m	9.84 yards / 19.7 yards	

Note: For special colors and measures, please contact our sales agent.



IMPORTANT NOTICE: The technical properties outlined are typical values and are not considered as specifications. Our terms and conditions of sale apply exclusively to orders and are excluding any liability for damages and injury of any kind, including consequential damages exceeding the purchase price. These properties are based on tests or conventional standards, PSTC, ASTM, NOM, Navitek's Technologies. It's important that the purchaser make its own test to determine the suitability of the product is to be use, no one is authorized by us to make guarantees orally. We reserve the right to make changes without notice or obligation in our products and publications.

Warranties and Limited Remedies:

Navilux, S.A. de C.V. warrants that each Navitek product meets the applicable Navitek specifications at the time Seller ships the product.

Individual products may have additional or different warranties, as stated on Navitek product packaging, package inserts, price pages or literature. Unless stated otherwise, if any product does not meet the applicable Navitek specification at the time of shipment, Navilux, S.A. de C.V.'s entire liability and purchaser's exclusive remedy will be replacement of Navitek product.

THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

Notice of defect must be received by Navilux, S.A. de C.V. within 90 days after the goods arrive at the designated place. Navilux, S.A. de C.V. has no obligations under this warranty with respect to products that have been modified through misuse, abuse, accident, neglect or mishandling by user or others.

Limitation of Liability:

Except where prohibited by law, Navilux, S.A. de C.V. will not be liable for any loss or damage arising from any Navitek product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. User is solely responsible for determining whether a Navitek product is fit for a particular purpose and suitable for user's method of application.