

512 NTK892

MANUAL GUMMED TAPE DISPENSER PREMIUM

Technical Data Sheet



Features

The NTK892 is a manual dispenser for water-activated tapes. It allows the user to pull, moisten, and cut the tape in a single motion, ensuring consistent sealing. It features both metric and standard scales, with 25 preset lengths. Its sturdy and portable design makes it suitable for use in various packaging areas.



Suggestion

Designed for sealing boxes and packages in small to medium production environments, it offers easy and quick handling.

Specifications	
Package Dimension (mm)	520 * 255 * 295
Product Dimension (mm)	470 * 275 * 248
Net Weight (kg)	9.6
Gross Weight (kg)	8.1
Tape Width (mm)	≤ 76
Dispensing Length (cm)	15 - 72
Diameter Roll (mm)	≤ 200
Water Reservoir Capacity (L)	2.3
Brushes	2 pieces
Pressure Plate Weight	3 pieces
Operating Temp Range (°C)	0 °C - +45 °C
Working Humidity Range (°C)	5% - 95% (non - condensation)



Product Application

Install the tape in the system with the gummed side facing down. Fill the water tank. Set the desired length using the selector dial and pull the lever. You will get a ready-to-use strip with a clean cut and proper moisture.





LIFETIME AND STORAGE

It is recommended to implement inventory rotation based on the 'first in, first out' (FIFO) principle.

IMPORTANT NOTICE: The technical properties outlined are typical values and are not considered as specifications. Our terms and conditions of sale apply exclusively to orders and are excluding any liability for damages and injury of any kind, including consequential damages exceeding the purchase price. These properties are based on tests or conventional standards, PSTC, ASTM, NOM, Navitek's Technologies. It's important that the purchaser make its own test to determine the suitability of the product is to be use, no one is authorized by us to make guarantees orally. We reserve the right to make changes without notice or obligation in our products and publications.



Warranty

Warranties and Limited Remedies:

Navilux, S.A. de C.V. warrants that each Navitek product meets the applicable Navitek specifications at the time Seller ships the product.

Individual products may have additional or different warranties, as stated on Navitek product packaging, package inserts, price pages or literature. Unless stated otherwise, if any product does not meet the applicable Navitek specification at the time of shipment, Navilux, S.A. de C.V.'s entire liability and purcharser's exclusive remedy will be repacement of Navitek product.

THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

Notice of defect must be received by Navilux, S.A. de C.V. within 90 days after the goods arrive at the designated place. Navilux, S.A. de C.V. has no obligations under this warranty with respect to products that have been modified through misuse, abuse, accident, neglect or mishandling by user or others.

Limitation of Liability:

Except where prohibited by law, Navilux, S.A. de C.V. will not be liable for any loss or damage arising from any Navitek product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability User is solely responsible for determining whether a Navitek product is fit for a particular purpose and suitable for user's method of application.