

512 NTK894

ELECTRIC GUMMED TAPE DISPENSER PREMIUM

Technical Data Sheet



Features

The NTK894 electric dispenser is designed for water-activated tapes. It automates the moistening and cutting process with precision, thanks to its touchscreen, infrared sensor, and programmable system for H-type sealing. Its compact, low-noise design makes it easy to operate in demanding environments. Compatible with various tape widths.



Suggestion

Recommended for medium to high-volume packaging operations where efficiency and consistent sealing are essential. Its compatibility with H-type applications makes it ideal for securing boxes quickly and reliably.

cations	
562 * 317 * 302	
510 * 252 * 266	
15.3	
13.4	
1	
100	
100-240	
50-60	
≤ 76	
≤ 200	
34	
1.73	
2 pieces	
3 pieces	
	562 * 317 * 302 510 * 252 * 266 15.3 13.4 1 100 100-240 50-60 ≤ 76 ≤ 200 34 1.73 2 pieces



Product Application

Fill the water tank and install the tape roll with the gummed side facing down. Set the length, quantity, and cutting mode on the touchscreen panel. Activate the machine to instantly get moistened and cut tape.



Lifetime and Storage

It is recommended to implement inventory rotation based on the 'first in, first out' (FIFO) principle.



IMPORTANT NOTICE: The technical properties outlined are typical values and are not considered as specifications. Our terms and conditions of sale apply exclusively to orders and are excluding any liability for damages and injury of any kind, including consequential damages exceeding the purchase price. These properties are based on tests or conventional standards, PSTC, ASTM, NOM, Navitek's Technologies. It's important that the purchaser make its own test to determine the suitability of the product is to be use, no one is authorized by us to make guarantees orally. We reserve the right to makechanges without notice or obligation in our products and publications.



Warranty

Warranties and Limited Remedies:

Navilux, S.A. de C.V. warrants that each Navitek product meets the applicable Navitek specifications at the time Seller ships the product.

Individual products may have additional or different warranties, as stated on Navitek product packaging, package inserts, price pages or literature. Unless stated otherwise, if any product does not meet the applicable Navitek specification at the time of shipment, Navilux, S.A. de C.V.'s entire liability and purcharser's exclusive remedy will be repacement of Navitek product.

THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

Notice of defect must be received by Navilux, S.A. de C.V. within 90 days after the goods arrive at the designated place. Navilux, S.A. de C.V. has no obligations under this warranty with respect to products that have been modified through misuse, abuse, accident, neglect or mishandling by user or others.

Limitation of Liability:

Except where prohibited by law, Navilux, S.A. de C.V. will not be liable for any loss or damage arising from any Navitek product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability User is solely responsible for determining whether a Navitek product is fit for a particular purpose and suitable for user's method of application.