



FEATURES

Yellow coloured tape with an acrylic water-based adhesive over a polypropylene film resulting in a easy-to-use and safe tape, friendly for the environment and non toxic. Manufactured with a system that make microscopic cuts that help our tape to be easy to slice with the hands.



PRODUCT APPLICATION

The perfect tape for school and office purposes, useful for wrap, paste, protect, repair and joint. Very easy-to-use.



COLORS

Natural 



SUGGESTION

Is essential that the surface on which the tape is applied is clear, dry and free of grease, oil and other contaminants.




LIFETIME AND STORAGE

The lifetime of this product is 1 year since fabrication, keeping it in its original boxes away from heat sources as, Direct sunlight or shelves next to the exterior roofs.

The floors cold and humidity could affect the product performance, the suitable conditions for storage are: 69,8 °F and 51% of relative humidity.

We recommend rotating the stock in the practice of "First in, first out".

Composition		Specification	
Backing	BOPP (Bi Oriented Polypropylene)		
Adhesive	Water-Based Acrylic		
Adhesive Activation	Pressure Sensitive		
Composition	Metric Unit	Standar Unit	Test Method
Backing Thickness	23 microns	0.9 mils	PSTC-133
Dry Adhesive Thickness	16 microns	0.6 mils	PSTC-133
Total Thickness	39 ± 1 microns	1.5 ± 0.039 mils	PSTC-133
Organic Solvent's Composition	0 %	0 %	N/A
Adhesive Properties	Metric Unit (Minimum Value)	Standar Unit (Minimum Value)	Test Method
Adhesion to Steel 180° (Peel)	450 g/inches	16 oz/inches	PSTC-101
Loop Tack (Stickness)	650 g/inches	23 oz/inches	PSTC-16
Shear 1"x1"x1kg (Holding Power)	50 hours	50 hours	PSTC-107
Primary Physical Properties	Metric Unit	Standar Unit	Test Method
Tensile Strength	30 ± 10% N/cm	17 ± 10% lb/inches	PSTC-131
Elongation	150 ± 20 %	150 ± 20 %	PSTC-131
Thermic / Electric Properties	Metric Unit	Standar Unit	Test Method
Minimum Temperature of Application	0 °C	32 °F	NTK
Maximum Temperature of Application	35 °C	95 °F	NTK
Measures 	Metric Unit	Standar Unit	
Width	12 mm	1/2 inches	
Length	2.5 m, 5 m, 10 m	2.7 yd, 5.4 yd, 11 yd	

Note: For special colors and measures, please contact our sales agent.



Warranties and Limited Remedies:

Navilux, S.A. de C.V. warrants that each Navitek product meets the applicable Navitek specifications at the time Seller ships the product.

Individual products may have additional or different warranties, as stated on Navitek product packaging, package inserts, price pages or literature. Unless stated otherwise, if any product does not meet the applicable Navitek specification at the time of shipment, Navilux, S.A. de C.V.'s entire liability and purchaser's exclusive remedy will be replacement of Navitek product.

THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

Notice of defect must be received by Navilux, S.A. de C.V. within 90 days after the goods arrive at the designated place. Navilux, S.A. de C.V. has no obligations under this warranty with respect to products that have been modified through misuse, abuse, accident, neglect or mishandling by user or others.

Limitation of Liability:

Except where prohibited by law, Navilux, S.A. de C.V. will not be liable for any loss or damage arising from any Navitek product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. User is solely responsible for determining whether a Navitek product is fit for a particular purpose and suitable for user's method of application.