

Double Face Tape: Nano Tek Technical Data Sheet



FEATURES

Nano-Tek Tape is made with advanced acrylic technology and features a transparent, flexible design suitable for a wide range of indoor and outdoor mounting applications. It provides strong, reliable adhesion on smooth surfaces such as glass, metal, ceramic, plastic, and marble.

The tape is removable without leaving residue, washable to restore adhesion, and reusable multiple times. Its durability and resistance to aging make it a practical alternative to nails, screws, and conventional adhesive tapes.



PRODUCT APPLICATION

Ideal for mounting and organizing items without nails or screws. Its transparent and reusable design makes it perfect for homes, offices, and commercial spaces.

Suitable for mirrors, picture frames, bathroom accessories, signs, decorations, and other lightweight objects on clean, smooth surfaces.



COLORS

Clear



RECOMMENDATIONS

For best performance, apply the tape to clean, dry surfaces free from dust, grease, oil, or moisture.

The tape is washable and reusable. Simply rinse with water, allow it to dry completely, and reuse. Remove carefully when used on delicate surfaces.



SHELF LIFE & STORAGE


Shelf life is 1 year from the date of manufacture when stored under recommended conditions.

Store the product in its original packaging, away from direct sunlight, heat sources, and excessive humidity. Recommended storage conditions are 15°C to 28°C (59°F to 82°F) with 40% to 70% relative humidity.

For inventory control, follow the FIFO ("First In, First Out") method.

Composition		Especificacion	
Liner		PET Film	
Adhesive		Acrylic	
Adhesive Activation		Pressure Sensitive	
Composition	Metric Unit	Standard Unit	Test Method
Liner Thickness	55 microns	2.1 mils	PSTC-133
Total Thickness	1000 microns	39.3 mils	PSTC-133
Adhesive Properties	Metric Unit (Minimum Value)	Standard Unit (Minimum Value)	Test Method
Adhesion to Steel 180° (Peel)	2000 g/inches	70.5 oz/inches	PSTC-101
Initial Tack	#10	#10	GB/T 4852-2002
Holding Power	80 hours	80 hours	GB/T 4851-1998
Measures	Metric Unit	Standard Unit	
Width	28 mm	1.1 inches	
Lenght	3,5 m	3.28, 5.46 yards	

Note: For special colors and measures, please contact our sales agent.



IMPORTANT NOTICE: The technical properties outlined are typical values and are not considered as specifications. Our terms and conditions of sale apply exclusively to orders and are excluding any liability for damages and injury of any kind, including consequential damages exceeding the purchase price. These properties are based on tests or conventional standards, ASTM, NOM, Navitek's Technologies. It's important that the purchaser make its own test to determine the suitability of the product is to be use, no one is authorized by us to make guarantees orally. We reserve the right to makechanges without notice or obligation in our products and publications.

Warranties and Limited Remedies:

Navilux, S.A. de C.V. warrants that each Navitek product meets the applicable Navitek specifications at the time Seller ships the product.

Individual products may have additional or different warranties, as stated on Navitek product packaging, package inserts, price pages or literature. Unless stated otherwise, if any product does not meet the applicable Navitek specification at the time of shipment, Navilux, S.A. de C.V.'s entire liability and purchaser's exclusive remedy will be replacement of Navitek product.

THE WARRANTY STATED ABOVE IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTY OF MERCHANTABILITY, THE IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING OR OF PERFORMANCE, CUSTOM OR USAGE OF TRADE.

Notice of defect must be received by Navilux, S.A. de C.V. within 90 days after the goods arrive at the designated place. Navilux, S.A. de C.V. has no obligations under this warranty with respect to products that have been modified through misuse, abuse, accident, neglect or mishandling by user or others.

Limitation of Liability:

Except where prohibited by law, Navilux, S.A. de C.V. will not be liable for any loss or damage arising from any Navitek product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability. User is solely responsible for determining whether a Navitek product is fit for a particular purpose and suitable for user's method of application.